

FSW17P - BRONZE

Spark Resistant Flange Spreading Wedge

A Spark Resistant Hydraulic Flange Spreading Wedge with a combined hydraulic cylinder and pump unit.

The FSW17P flange spreading wedge can enter a flange joint access gap as small as 6mm and produce a maximum force of 326kN when used in pairs (as recommended) to push the mating faces of flanges apart. The FSW17P can create a gap up to 81mm between flange faces with the stepped blocks fitted facilitating the replacement of gaskets, seal ring's, or other flange face maintenance and testing.

- 100% Load/Pressure tested and certified
- High durability High Quality low Maintenance design
- Tool weight 8.5Kg
- Max Spreading force 163kN (326kN when used in pairs)
- Spreading distance 6mm to 81mm when used with stepped blocks
- Robust Moulded Case for easy transportation and storage




Engineered Energy Equipment

Product Sales Product Rental Bespoke Solutions

FSW17P - BRONZE

Flange Spreading Wedge





Kit weight: 13Kg

Kit Dims.: 580mm x 340mm x 180mm

Tool Weight: 8.5Kg

Tool Dims.: 76mm x 155mm x 440mm

Product ordering code: FSW17P - BRONZE

Kit Content

- 1 x FSW17P-BRONZE Tool with combined hydraulic cylinder and pump unit
- 1 x Pump Actuating Handle
- 1 x Non Ferrous Safety Block
- 1 x Safety Lanyard
- 2x Bronxe Stepped Blocks with securing screws and allen key
- 1 x Instruction Manual
- 1 x Robust moulded carry case



Engineered Energy Equipment

Product Sales Product Rental Bespoke Solutions

www.renquip.com