

FSW9K - BRONZE

Spark Resistant Flange Spreading Wedge

A Spark Resistant Mechanical Flange Spreading wedge actuated by applying torque.

The FSW9 flange spreading wedge can enter a flange joint access gap as small as 6mm (0.24") and produce a maximum spreading force of 188kN (18.8T) when used in pairs (as recommended) to push the mating faces of flanges apart.

The FSW9 can create a gap up to 81mm (3.19") between flange faces with the stepped blocks fitted facilitating the replacement of gaskets, seal rings, or other flange face maintenance and testing.

- 100% Load/Pressure tested and certified
- High durability, High Quality, Low Maintenance
- Tool weight
5.5Kg (12.1lbs)
- Max Spreading force
94kN (9.4T)
- Spreading distance
6mm (0.24") to 81mm (3.19")
- Robust Moulded Case




Engineered Energy Equipment

Product Sales | Product Rental | Bespoke Solutions

www.renquip.com

FSW9K - BRONZE

Flange Spreading Wedge



Max Spreading Force: 94kN (9.4T)

Max Applied Torque : 200Nm (150ft.lb)

Kit weight: 12Kg (26.5lbs)

Kit Dims.: 580mm x 340mm x 180mm
(22.8" x 13.4" x 7.1")

Tool Weight: 5.5Kg

Tool Dims.: 80mm x 160mm x 290mm
(3.1" x 6.3" x 11.4")

Product ordering code: FSW9K-BRONZE

Kit Content

- 1 x FSW9 Bronze Jaw Tool
- 1 x Safety Block
- 2 x Bronze Stepped Blocks with securing screws and allen key
- 1 x 200Nm (150ft.lb) Torque Wrench
- 1 x 22mm (1/2") Drive socket
- 1 x Instruction Manual
- 1 x Robust Moulded Carry Case with foam insert
- 1 x Safety Lanyard



Engineered Energy Equipment

Product Sales | Product Rental | Bespoke Solutions

www.renquip.com

Unit 1 Dunnottar House, Howe Moss Drive, Dyce, Aberdeen, AB21 0FN
+44(0) 1224001861 | info@renquip.com